

# Releasit Encap-Clean DS2

SDS Number: Releasit 511189 SDS

Revision Date: 3/2/2019

Page 1 of 5

# PRODUCT AND COMPANY IDENTIFICATION

Manufacturer Releasit

8925 66th Court #101 Pinellas Park, FL 33782

Phone: Web: Emergency:

800-330-1888 www.releasit.com INFOTRAC 1-800-535-5053 (North America) 1-352-323-3500 (International)

Product Identifier:	Releasit Encap-Clean DS2
SDS Number:	Releasit 511189 SDS
Product Code:	511189
Revision Date:	3/2/2019
Version:	2
Product Use:	Carpet Cleaning

## HAZARDS IDENTIFICATION

### **Classification of the Substance or Mixture**

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS): Health, Serious Eye Damage/Eye Irritation, 2 A

### **GHS Label Elements, Including Precautionary Statements**

### **GHS Signal Word: WARNING**

#### **GHS Hazard Pictograms:**



#### **GHS Hazard Statements:**

H319 - Causes serious eye irritation

#### **GHS Precautionary Statements:**

P210 - Keep away from heat/sparks/open flames/hot surfaces.

P233 - Keep container tightly closed.

P264 - Wash skin thoroughly after handling.

P280f - Wear eye protection/face protection.

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.

P302 + P352 - IF ON SKIN: Wash with plenty of water/...

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.


P501 - Dispose of contents/ container to an approved waste disposal plant.



# **Releasit Encap-Clean DS2**

### SDS Number: Releasit 511189 SDS

NFPA:Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = NoneHMIS III:Health = 1, Fire = 0, Physical Hazard = 0HMIS PPE:B - Safety Glasses, Gloves



## COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:			
CAS#	%	Chemical Name:	
67-63-0	<4.0%	2-Propanol	

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

4	FIRST AID MEASURES	
Inhalation:	Give oxygen or artificail respiration if needed.	
Skin Contact:	Promptly flush skin with water until all chemical is removed. Get medical attention if needed.	
Eye Contact:	Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. If systom persist, call a physician.	
Ingestion:	Do not induce vomiting. Seek immediate medical attention. Drink large quantities of water.	

5	FIRE FIGHTING MEASURES
Flammability:	N/A
Flash Point:	N/A
Flash Point Method:	N/A
Burning Rate:	N/A
Autoignition Temp:	N/A
LEL:	N/A
UEL:	N/A
Dry powder foam carbo	on dioxide. Wear self contained breathing apparatus and other protective clothing

Dry powder, foam, carbon dioxide. Wear self contained breathing apparatus and other protective clothing.

### ACCIDENTAL RELEASE MEASURES

Wear appropriate personal protective equipment Eliminate all sources of ignition. Watch out for slippery conditions when spillage. Avoid contact with eyes.

Ventilate area and wash spill site after material pickup is complete.

# Safety Data Sheet

Revision Date: 3/2/2019

Page 2 of 5



# Safety Data Sheet

# Releasit Encap-Clean DS2

### SDS Number: Releasit 511189 SDS

Revision Date: 3/2/2019

Page 3 of 5

7	HANDLING AND STORAGE		
Handling Precautions:	open flame, excessive heat, or o	direct sunlight.	in, or clothing. Do not expose containers to each of children. Wash thoroughly after
Storage Requirements:	Keep away from heat, sparks, a	nd flames.	
8	EXPOSURE CONTROLS/PERS	ONAL PROTECTION	
Personal Protective Equipment:	Goggles; Gloves;		
2-Propanol cas#:(67-63-	-0) [<4.0%]		
Components with workpl	ace control parameters		
TWA 200 ppm	USA. ACGIH Threshold Limit Value	es	
Eye & Upper Respiratory Central Nervous System Not classifiable as a hum	impairment		
STEL 400 ppm	USA. ACGIH Threshold Limit Value	es	
Eye & Upper Respiratory Central Nervous System Not classifiable as a hurr	impairment		
TWA 400 ppm 980 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	r	
STEL 500 ppm 1,225 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	r	
TWA 400 ppm 980 mg/m3	USA. Occupational Exposure Limit (OSHA) - Table Z-1 Limits for Air	S	
The value in mg/m3 is ap	Contaminants oproximate.		
TWA 400 ppm 980 mg/m3	USA. NIOSH Recommended Exposure Limits		
ST 500 ppm 1,225 mg/m3	USA. NIOSH Recommended Exposure Limits		
9	PHYSICAL AND CHEMICAL PR	OPERTIES	
Appearance:	Translucent Liquid		
Physical State:	Liquid	Odor:	Clean Scent
Odor Threshold:	No Information Available	Molecular Formula:	No Information Available
Particle Size: Spec Grav./Density:	No Information Available 1.032 +/005	Solubility: Softening Point:	Completely Soluble No Information Available
Viscosity:	No Information Available	Percent Volatile:	No Information Available
		. or conter oracine.	

Saturated Vapor<br/>Concentration:No Information AvailableBoiling Point:Approximately 100C / 212FFlammability:No Information Available

Freezing/Melting Pt.: Flash Point:

Heat Value:

No Information Available No Information Available No Information Available

No Information Available No Information Available



# Safety Data Sheet

# **Releasit Encap-Clean DS2**

#### SDS Number: Releasit 511189 SDS

Revision Date: 3/2/2019

Page 4 of 5

Partition Coefficient:No Information AvailableVapor Pressure:No Information AvailablepH:9.5 +/-.5Evap. Rate:Similiar to waterMolecular weight:No Information AvailableDecomp Temp:No Information Available

Octanol: Vapor Density: VOC: Bulk Density: Auto-Ignition Temp: UFL/LFL:

No Information Available No Information Available <4.0% No Information Available No Information Available No Information Available

### STABILITY AND REACTIVITY

Reactivity:	None under normal processing
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	Heat, Flames and sparks
Materials to Avoid:	Strong oxidizers, alkalis and acids
Hazardous Decomposition:	Ammonia vapors. If burned, normal combustion products: Carbon dioxide,Carbon Monoxide, Nitrogen oxides
Hazardous Polymerization:	Will not occur.

# **TOXICOLOGICAL INFORMATION**

2-Propanol cas#:(67-63-0) [<4.0%]

Information on toxicological effects

Acute toxicity: LD50 Oral - rat - 5,045 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Somnolence (general depressed activity). LC50 Inhalation - rat - 8 h - 16000 ppm LD50 Dermal - rabbit - 12,800 mg/kg no data available

Skin corrosion/irritation: Skin - rabbit Result: Mild skin irritation

Serious eye damage/eye irritation: Eyes - rabbit Result: Eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol) NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: NT8050000

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects. Kidney - Irregularities - Based on Human Evidence

# Safety Data Sheet



SDS Number: Releasit 511189 SDS

Revision Date: 3/2/2019

Page 5 of 5

12

# ECOLOGICAL INFORMATION

2-Propanol cas#:(67-63-0) [<4.0%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 9,640.00 mg/l - 96 h. Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 5,102.00 mg/l - 24 h. other aquatic invertebrates Immobilization EC50 - Daphnia magna (Water flea) - 6,851 mg/l - 24 h Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - > 2,000.00 mg/l - 72 h. EC50 - Algae - > 1,000.00 mg/l - 24 h

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

# DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

## TRANSPORT INFORMATION

Not Regulated

## **REGULATORY INFORMATION**

[%] RQ (CAS#) Substance - Reg Codes

[<4.0%] 2-Propanol (67-63-0) MASS, NJHS, NRC, OSHAWAC, PA, SARA313, TSCA, TXAIR

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

#### Regulatory Code Legend

MASS = MA Massachusetts Hazardous Substances List NJHS = NJ Right-to-Know Hazardous Substances NRC = Nationally Recognized Carcinogens OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances SARA313 = SARA 313 Title III Toxic Chemicals TSCA = Toxic Substances Control Act TXAIR = TX Air Contaminants with Health Effects Screening Level

# OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for suchmaterial used in combination with any other materials or in any other process, unless specified in the text.